

Model DSC1200 Fiber Optic Dynamic Signal Conditioner

DavidsonSensors™ provide the safest, most reliable and cost-effective instrumentation for harsh industrial applications.

This product data sheet describes Model DSC1200 dynamic high frequency signal conditioner. This universal signal conditioner may be multiplexed with any combination of Davidson dynamic transducers including: pressure, load, vibration, acceleration, and position.

This unit will interrogate up to eight sensors and is packaged in a 19" rackmount enclosure. The standard output is +/-5 Volts.



*Dynamic High Frequency Response
Signal Conditioner*

Functional Specifications

Channels

4 - 8 Channels

Input Power

120/240 VAC; 50-60Hz; 10 Watts

Output Signal

+/- 4.5 Volts

Temperature Limits

32°F to 120°F

Humidity Limits

0 to 100% relative humidity

Transmission Range

1000 feet

Displacement Range

11,000 to 20,000 nm

Fiber Specification

62.5/125 Multimode

Physical Specifications

Size

19" Rackmount x 3U High 4 Channel
19" Rackmount x 6U High 8 Channel

Weight

15 lbs

Signal Output Connectors

External BNC Connectors

Fiber Optic Sensor Connectors

External ST Bulkhead

Performance Specifications

Displacement Accuracy

3% of Full Scale

Frequency Response

2 Hz to 5 kHz (3dB down)
5 Hz to 4 kHz (+/- 0.4 dB)


Dynamic Range

45 dB with averaging

Theory of Operation

A fiber optic signal conditioner is the equivalent of a transmitter in conventional electronic sensing systems. During operation, the signal conditioner sends a continuous stream of light to each of the transducers. The light signal received from each transducer is split and projected onto two photodiodes. The interferometer acts as an optical cross-correlator and instantly converts the modulated light into a cross-correlated signal. The two cross-correlated signals maintain a phase relationship with one another.

The light signal is converted into electronic signals that are processed by a microprocessor. The microprocessor in the signal conditioner converts the signals into a known change in the length of the sensor gap. The calibration constants are known for each transducer and loaded into the microprocessor. The microprocessor converts the known gap into an analog output signal, i.e. +/- 5 Volts, proportional to the engineering units, (i.e. psig), for the transducer. The result is unprecedented measurement accuracy and frequency response in harsh industrial environments.



Fiber Optic Pressure Sensing Diaphragm

Fiber Optic Sensing Advantages

Fiber optic sensing offers a number of advantages for measurement in harsh industrial environments. DavidsonSensors™ are intrinsically-safe, immune to electromagnetic interference, and suitable for continuous use at temperatures up to 1000°F.

Although fiber optic sensing systems can be used effectively even in benign environments, Davidson fiber optic sensing systems offer significant technical advantages when used in the following environments:

- Hot, Corrosive Environments
- Explosion Hazardous Areas
- High EMI Areas

Fiber optic sensing systems eliminate or mitigate many of the following common problems:

- Failure and Drift due to Hydrogen Permeation
- Drift due to Fill-Fluid Leaks
- Failure due to Lightning
- Problems due to Ground Potential
- Noise due to EMI/RFI
- Costs of Nitrogen Purge Systems

Testing and Calibration

Calibration is performed over the entire displacement range at 72° F.

Documentation

A user’s manual is included with each unit.

Tagging

Stainless steel tags will be permanently attached to each signal conditioner upon request.

Other Applications

For information about other Davidson products, see www.davidson-instruments.com

Guide to Configuring a Fiber Optic Sensing System

For information to assist you in planning a fiber optic sensing system, see www.davidson-instruments.com

Ordering Data

Model Number	DSC1200	
Channels	4 8	4 8
Fiber Optic Connector Type	1 2	ST Other
Other Specifications*	0 1	No Yes

* Tagging, documentation, other instructions etc.

Ordering Data Worksheet

Unit Number	Model Number	Number of Channels	Fiber Optic Connector Type	Other Specifications
1	DSU1200			
2	DSU1200			
3	DSU1200			
4	DSU1200			
5	DSU1200			
6	DSU1200			

U.S. Patent Pending

Davidson Instruments, Inc.
8301 New Trails Drive
The Woodlands, TX 77381 USA

Telephone: 281-362-4900
Fax: 281-362-4933
sales@davidson-instruments.com
www.davidson-instruments.com

© 2006 Davidson Instruments, Inc.